



CM24XS-RR

*NOTE: Countertop Merchandisers are manufactured to order and are not returnable

PRODUCT INFORMATION

(see CM Spec Sheet for complete details)

STANDARD FEATURES: Self-contained forced air refrigeration system for uniform cooling of product • Automatic condensate evaporator • Digital thermostat with automatic defrost • All stainless steel interior construction • Stainless steel exterior construction with galvanized steel bottom • Removable condenser air inlet filter for easy cleaning • Nine-foot grounded cord & plug provided • Available with stainless steel door or glass door with stainless steel frame • Two adjustable coated shelves • Interior LED light included • Listed to NSF standard 7 for open food as a storage refrigerator

CAPACITY: 4.7 cu. ft.

ELECTRICAL: 120V, 1 phase, 60Hz, 2.5 full load amps. Dedicated 15 amp circuit is required

REFRIGERATION: 1/8 HP, R290 refrigerant

PLUMBING: Automatic condensate evaporator. No drain connection required.

COUNTERTOP MERCHANDISER

Standard List = \$7,533

Weight = 190#

CM24 -

Door Style:

SS = Stainless Front and Back Door

SX = Stainless Front and Glass Back Door - Add \$560

XS = Glass Front and Stainless Back Door - Add \$560

XX = Glass Front and Glass Back Door - Add \$1,120

Rear Door Hinge Location:

L = Left or R = Right

Front Door Hinge Location:

L = Left or R = Right

ACCESSORIES

MODEL	DESCRIPTION	LIST	WGT
LCLS	4" legs with adjustable flanged feet	\$297	5#
CE-220/50S	Convert self-contained unit to 220V/50Hz electrical	\$307	N/A

Wall-Mount Refrigerators



WMR24S-R

PRODUCT INFORMATION

(see WMR Spec Sheet for complete details)

STANDARD FEATURES: Self-contained forced air refrigeration system for uniform cooling of product • Automatic condensate evaporator • Digital thermostat with automatic defrost • All stainless steel interior construction • Stainless exterior construction with galvanized back and bottom • Available with stainless steel door or glass door with stainless steel frame • Two adjustable coated shelves • Removable condenser air inlet filter for easy cleaning • Bracket for wall mounting • Nine-foot grounded cord & plug provided • Interior LED light included • Listed to NSF standard 7 for open food as a storage refrigerator

CAPACITY: 3.9 cu. ft.

ELECTRICAL: 120V, 1 phase, 60Hz, 2.5 full load amps. Dedicated 15 amp circuit is required.

REFRIGERATION: 1/8 HP, R290 refrigerant

PLUMBING: Automatic condensate evaporator. No drain connection required.

WALL-MOUNT REFRIGERATORS

MODEL	LIST	DOOR STYLES	HINGE	WGT
WMR24S-L	\$6,536	Stainless	Left	165#
WMR24S-R	\$6,536	Stainless	Right	165#
WMR24X-L	\$7,100	Glass	Left	165#
WMR24X-R	\$7,100	Glass	Right	165#

ACCESSORIES

MODEL	DESCRIPTION	LIST	WGT
LCLS	4" legs with adjustable flanged feet	\$297	5#
CE-220/50S	Convert self-contained unit to 220V/50Hz electrical	\$307	N/A

Kitchen Fabrication & Refrigeration