

There are ten different GT-18 models to choose from.

The top of every GT-18 glasswasher is removable. The same base, which houses all the electrical and mechanical components, is used with all of the different top styles. The various tops are used in different situations to increase glasswasher throughput. A suffix is added to the GT-18 model number to specify a top different than the standard door type. The different models are pictured below:



GT-18
Front load door type



GT-18+1
Front-to-back
pass thru



Cocktail server view
with simulated bar
top and bar die



GT-18+1L
Front-to-side pass thru with left side
drain table (GT-18+1R with right side
drain table is also available)



GT-18+2
Side-to-side
pass thru



GT-18+2-IC
Side-to-side corner
pass thru

PRODUCT INFORMATION

(see GT-18, GT-18+1, GT-18+1L or R, GT-18+2, GT-18+2 Ext, GT-18+2-IC, and GT-18 Access Spec Sheets for complete details)

STANDARD FEATURES:

- Drive wheel and glass rack lift out for cleaning
- Two 16" diameter polypropylene racks included
- Spray box unlatches for easy cleaning and visual inspection - 15 spray nozzles have been engineered for maximum soil removal
- Digital temperature gauge built into switch panel
- Intelligent microprocessor control delays cycle start, up to two minutes, when incoming water is below 120°F (49°C)
- Automatic peristaltic metering pumps accurately dispense detergent, sanitizer and rinse aid
- Prime Switch for quick chemical priming
- 1/6 HP pump recirculates wash water and rinse water
- Fractional HP drive motor powers the belt driven rotary rack and includes built-in slip clutch

ELECTRICAL:

- 120V, single phase, 60Hz, 6-foot grounded cord and plug included

CAPACITY:

- 2 minute cycle, 70 second wash and 22 second rinse exposure
- 720 - 2-1/2" diameter or 360 - 3-1/4" diameter glasses per hour (maximum glass height 10" - including pitchers and wine carafes)

EXTENDED GT-18+2 MODELS

Extended GT-18+2 models have the drain table extended on one side of the glasswasher to hold more than one rack. This increases overall glasswasher throughput by allowing multiple racks of glassware to be pre-loaded for washing. The model number specifies the overall glasswasher length and the location of the extended drain table. For example, the GT-18+2-78L (pictured) is 78" long overall and has the left side drain table extended. Extended +2's are available in 78" and 90" overall lengths. The 78" models come with three racks and the 90" models come with four racks. A leg set is included under the extended drain table.



GT-18+2-78L with 01000708 glass rack holder

Glasswashers

ROTARY RACK GLASSWASHERS

MODEL	DESCRIPTION	LIST	WEIGHT	LENGTH	DRAIN TABLE
GT-18	Front load door type	\$14,381	145#	18"	N/A
GT-18+1	Front-to-back pass thru	\$15,496	155#	18"	Back
GT-18+1L	Front-to-side pass thru	\$16,131	175#	36"	Left
GT-18+1R	Front-to-side pass thru	\$16,131	175#	36"	Right
GT-18+2	Side-to-side pass thru	\$16,887	195#	60"	Left & Right

CUSTOM ROTARY RACK GLASSWASHERS*

MODEL	DESCRIPTION	LIST	WEIGHT	LENGTH	DRAIN TABLE
GT-18+2-IC	Side-to-side corner pass thru	\$18,008	245#	42" x 42"	Left & Right
GT-18+2-78L	Side-to-side pass thru, left extended	\$17,837	275#	78"	Left & Right
GT-18+2-78R	Side-to-side pass thru, right extended	\$17,837	275#	78"	Left & Right
GT-18+2-90L	Side-to-side pass thru, left extended	\$18,472	300#	90"	Left & Right
GT-18+2-90R	Side-to-side pass thru, right extended	\$18,472	300#	90"	Left & Right

*NOTE: These units are manufactured to order and are not returnable

ACCESSORIES

MODEL	DESCRIPTION	LIST	WEIGHT
01000532	Glass rack	\$176	2#
01000533	Dish rack	\$337	4#
01000536	Glass rack insert for stemware	\$635	6#
01000710	Clip-on chemical rail	\$478	10#
01000706	Glass rack holder (for GT-18+1 only)	\$607	10#
01000708	Glass rack holder (+2, +1L, or +1R models)	\$1,225	20#
01000709	Glass rack holder w/shelf (+2, +1L, or +1R models)	\$1,536	25#
01000557	Export transformer†	\$2,210	20#



GT-18 with 01000710 chemical rail



01000536 Glass rack insert for stemware



01000533 Dish rack

See underbar section for wet waste sinks and drainboards.

†EXPORT TRANSFORMER- The export transformer converts the electrical requirement to 220V, 1 phase, 50Hz.



GT-18+2 with SWA-12 wet waste sink and 01000709 glass rack holder



GT-18+1 with 01000706 glass rack holder



GT-18+2-78L with 01000708 glass rack holder