



**PRODUCT INFORMATION**

(see LC Spec Sheet for complete details)

**STANDARD FEATURES:**

- Self-contained forced air refrigeration system for uniform cooling of product
- Automatic condensate evaporator
- Digital thermostat with automatic defrost
- All stainless steel interior construction
- Stainless steel foamed-in-place insulated door and lettuce chute
- Stainless exterior construction with galvanized back and bottom
- Removable plastic lettuce bin and divider included
- Removable condenser air inlet filter for easy cleaning
- Bracket for wall mounting
- 4" adjustable legs available
- Nine-foot grounded cord & plug provided
- Listed to NSF standard 7 for open food as a storage refrigerator

**CAPACITY:** Approx. 50 heads of lettuce (shredded)

**ELECTRICAL:** 120V, 1 phase, 60Hz, 2.5 full load amps. Dedicated 15 amp circuit is required.

**REFRIGERATION:** 1/8 HP, R290 refrigerant, 1,023 BTU/hr heat rejection

**PLUMBING:** Automatic condensate evaporator. No drain connection required.



LC-BIN lettuce bin with LC-BDIV bin divider

**LETTUCE CRISPER**

MODEL	DESCRIPTION	LIST	WGT
LC	24" Lettuce Crisper with plastic bin, stainless bin divider, & wall-mounting bracket	\$7,021	185#

**ACCESSORIES**

MODEL	DESCRIPTION	LIST	WGT
LC-BIN	Plastic lettuce bin (additional)	\$398	15#
LC-BDIV	Lettuce bin divider, stainless steel (additional)	\$127	5#
LCLS	4" legs with adjustable flanged feet	\$297	5#
CE-220/50S	Convert self-contained unit to 220V/50Hz electrical	\$307	N/A